



**Commonwealth
of Australia**

Gazette

No. TC 16/44, Wednesday, 16 November 2016
Published by the Commonwealth of Australia

TARIFF CONCESSIONS

CONTENTS

| | |
|--|---|
| TCO Applications | 2 |
| TCOs Made | 6 |
| Local Manufacturer Initiated - TCO Revocation Requests | 9 |

The Commonwealth of Australia Tariff Concessions Gazette
(the Tariff Concessions Gazette) is free of charge on the DIBP
internet site at: <http://www.border.gov.au>

The Tariff Concessions Administration Section is located at
5 Constitution Ave Canberra City 2601

Contact details:

General Email Inquiries:.....tarcon@border.gov.au
General Inquiries:(02) 6229 3567
TAPIN help desk:(02) 6275 6534
Facsimile:.....(02) 6223 8180

CUSTOMS ACT 1901 - NOTICE PURSUANT TO SECTION 269K(1) - APPLICATIONS MADE FOR TARIFF CONCESSION ORDERS

Applications have been lodged for Tariff Concession Orders for the goods described in the following TABLE.

Australian manufacturers who wish to contest the granting of a Tariff Concession Order for the goods described are invited to lodge a submission in writing in an approved form. Submissions must be lodged within 50 days of the date of publication of this Notice.

The operative date (Op.) and TC reference number follow the description of goods.

To assist local manufacturers, the use(s) to which the goods can be put follow the description of goods.

Objections to the making of TCO submission forms are available at

<http://www.border.gov.au/Forms/Documents/b444.pdf>

Contact: Email tarcon@border.gov.au

THE TABLE

| Description of Goods including the Customs Tariff Classification | Schedule 4 Item Number General Duty Rate |
|--|---|
| 3506.91.00 ADHESIVE, waterborne, having a basis of polychloroprene Op. 12.10.16 Stated Use: As a rolling adhesive in the foam processing industry Applicant: AUSTRALIAN COMFORT GROUP PTY LTD | - TC 1659311 5% |
| 3926.90.90 KITS, POWER CABLE JOINER NOT GREATER THAN 1 kV WITH OR WITHOUT RING CONNECTOR AND/OR STIRRER, consisting ALL of the following: (a) joint housing; (b) cable seals; (c) joining compound; (d) abrasive cloth tape; (e) gloves Op. 25.10.16 | - TC 1662848 5% |
| 4810.29.90 LABEL PAPER, in rolls, having ALL of the following: (a) facestock base weight NOT less than 71 gsm and NOT greater than 89 gsm; (b) rubber based adhesive; (c) glassine liner Op. 20.10.16 Stated Use: Printing paper utilised in the manufacture of labels Applicant: AVERY DENNISON MATERIALS PTY LTD | - TC 1661806 5% |

| Description of Goods including the Customs Tariff Classification | Schedule 4 Item Number General Duty Rate |
|--|---|
| <p>7907.00.90 ANODES, SACRIFICIAL ZINC, being EITHER of the following: (a) embedded galvanic anode units, including ALL of the following: (i) zinc anode core; (ii) steel tie wires; (iii) cement based mortar shell, (b) distributed anode system, having a zinc composition of NOT less than 50%, including BOTH of the following: (i) zinc AND steel core; (ii) steel tie wires Op. 14.10.16</p> <p>Stated Use: To control on-going corrosion and to prevent the initiation of new corrosion activity in concrete structures</p> <p>Applicant: PARCHEM CONSTRUCTION SUPPLIES PTY LTD</p> | <p>50</p> <p>- TC 1659798</p> |
| <p>8418.69.00 FREEZER AND/OR COOL ROOMS, including BOTH of the following: (a) high-density polyurethane panels; (b) cooler AND/OR freezer unit Op. 25.10.16</p> <p>Stated Use: Cold room storage</p> <p>Applicant: SKOPE INDUSTRIES LIMITED</p> | <p>50</p> <p>- TC 1663112</p> <p>5%</p> |
| <p>8419.90.00 PARTS, GAS HEATED REFORMER, being cartridge assemblies having ALL of the following: (a) structural steel frames; (b) tubes; (c) tube sheets; (d) baffles; (e) tie-rods; (f) board AND wool insulation Op. 12.10.16</p> <p>Stated Use: Part of the reforming system in an ammonia plant</p> <p>Applicant: INCITEC PIVOT LIMITED</p> | <p>50</p> <p>- TC 1658867</p> <p>5%</p> |
| <p>8421.31.00 AIR FILTERS, GARDEN OR FORESTRY TOOL, INTERNAL COMBUSTION ENGINE Op. 14.10.16</p> <p>Stated Use: As air filters for goods such as chainsaws and brush cutters</p> <p>Applicant: STIHL PTY LTD</p> | <p>50</p> <p>- TC 1660230</p> <p>5%</p> |
| <p>8421.99.00 PARTS, GAS TURBINE AIR INTAKE FILTER, being frame assemblies with OR without sealant cartridge having ALL of the following: (a) stainless steel frames; (b) steel bolts; (c) steel screws; (d) steel nuts; (e) steel washers Op. 12.10.16</p> <p>Stated Use: To support and secure air intake filters at the air intake area of a gas turbine</p> <p>Applicant: GLNG OPERATIONS PTY LTD</p> | <p>50</p> <p>- TC 1658946</p> <p>5%</p> |

| Description of Goods including the Customs Tariff Classification | Schedule 4 Item Number General Duty Rate |
|---|--|
| 8427.10.00 MUSHROOM HARVESTER TRUCKS, self-propelled, battery powered, electric motor, ride-in operated, height adjustable hydraulic lift, having ANY of the following: (a) picking racks; (b) weighing scales; (c) battery charger; (d) NOT less than 4 wheels Op. 24.10.16 | 50 - TC 1662478 |
| Stated Use: Transport mushroom pickers along rows of beds at various heights | |
| Applicant: PREMIER MUSHROOMS PTY.LTD | 5% |
| 8428.90.00 PULLERS, ALUMINIUM EXTRUSION HANDLING, motorised, rail mounted, programmable logic controlled, un-assembled, having ALL of the following; (a) pliers; (b) rails; (c) encoder; (d) locking jaws; (e) cable drive Op. 20.10.16 | 50 - TC 1661809 |
| Stated Use: Pulling of aluminium extrusions during the manufacturing process | |
| Applicant: G JAMES AUSTRALIA PTY LTD | 5% |
| 8481.80.90 VALVES, sleeve actuated AND/OR regulated, axial flow, pilot valve controlled Op. 10.10.16 | 50 - TC 1658581 |
| Stated Use: For firewater on/off activation, and/or pressure regulating/sustaining in pipework | |
| Applicant: SEMCO MARITIME PTY LTD | 5% |
| 8482.80.00 SLEW RING BEARINGS, GERMINATING AND/OR KILN VESSEL Op. 19.10.16 | 50 - TC 1661455 |
| Stated Use: For turntable and pivot mounted support of germinating and kilning vessels | |
| Applicant: COOPERS BREWERY LIMITED | 5% |
| 8516.60.00 OVENS, STEAM AND MICROWAVE AND/OR DRY HEAT, electric powered, having ALL of the following: (a) volume capacity NOT less than 30 L and NOT greater than 69 L; (b) heat sensor; (c) steam controller; (d) convectional fan Op. 14.10.16 | 50 - TC 1660232 |
| Stated Use: For cooking food | |
| Applicant: V-ZUG AUSTRALIA PTY LTD | 5% |

| Description of Goods including the Customs Tariff Classification | | Schedule 4 Item Number General Duty Rate |
|---|---|---|
| 8516.60.00 | OVENS, DRY HEAT, electric powered, having a volume capacity NOT less than 40 L and NOT greater than 69 L Op. 14.10.16 Stated Use: For cooking food Applicant: V-ZUG AUSTRALIA PTY LTD | 50 - TC 1660234 5% |
| 8543.30.00 | ANODES, IMPRESSED CURRENT CATHODIC PROTECTION, including BOTH of the following: (a) ceramic anode body incorporating an imbedded titanium wire; (b) internal gas vents Op. 14.10.16 Stated Use: To facilitate electrolysis to mitigate corrosion in steel framed concrete structures Applicant: PARCHEM CONSTRUCTION SUPPLIES PTY LTD | 50 - TC 1659778 5% |
| 8608.00.00 | TRAMWAY TURNOUT ASSEMBLIES, consisting of BOTH of the following: (a) switches; (b) machined crossing frogs, with OR without drive earth boxes AND welded on rails Op. 17.10.16 Stated Use: For permitting trains or trams to leave a given track and travel to a branching track or parallel track Applicant: VOSSLOH COGIFER AUSTRALIA PTY LTD | 50 - TC 1660397 5% |
| 9406.00.00 | FREEZER AND/OR COOL ROOMS, modular, having high-density polyurethane panels, without freezing OR cooling units Op. 20.10.16 Stated Use: Cold room storage Applicant: SKOPE INDUSTRIES LIMITED | 50 - TC 1661626 5% |

CUSTOMS ACT 1901 - NOTICE PURSUANT TO SECTION 269R(1) - TARIFF CONCESSION ORDERS MADE

Tariff Concession Orders have been made for the goods described in the following TABLE.

The operative date (Op.) and TC reference No. follow the description of goods.

Local manufacturers of substitutable goods may request the revocation of TCOs at any time.

THE TABLE

| Description of Goods including the Customs Tariff Classification | Schedule 4 Item Number |
|---|------------------------|
| 3926.30.90 COMPONENTS, DOOR OR DRAWER, being ANY of the following: (a) drawer opening activation interfaces; (b) synchronisation linkages; (c) drawer spacing rods; (d) front gap template; (d) slider AND/OR runner fittings; (e) synchronisation adaptors Op. 23.08.16 Dec. date 14.11.16 - TC 1644685 | 50 |
| 4811.41.90 PAPER, on reels, having BOTH of the following: (a) weight NOT less than 70 gsm and NOT greater than 80 gsm; (b) water based repositionable pressure sensitive adhesive layer Op. 19.08.16 Dec. date 14.11.16 - TC 1643586 | 50 |
| 6306.22.00 TENTS, conical, including ALL of the following: (a) adjustable ventilator cap; (b) diameter NOT less than 5.5 metres; (c) height NOT less than 3.6 metres and NOT greater than 9 metres; (d) wooden poles, length NOT greater than 10 metres; (e) weight NOT less than 120 kg and NOT greater than 800 kg; (f) connector fittings, being ANY of the following: (i) head sections; (ii) pins; (iii) cross poles, (g) woven, one piece canvas, having ALL of the following: (i) capable of covering an area NOT less than 24 square metres; (ii) smoke development index NOT greater than 5, in accordance with standard AS 1530; (iii) spread of flame index NOT greater than 6, in accordance with standard AS 1530 Op. 18.08.16 Dec. date 14.11.16 - TC 1643580 | 50 |
| 8418.69.00 SOFT SERVE ICE CREAM AND THICK SHAKE MACHINES, including ALL of the following: (a) mix level AND temperature sensors; (b) peristaltic pump syrup delivery unit; (c) pasteuriser; (d) soft serve AND shake dispensing units; (e) two freezers; (f) touch panel Op. 16.08.16 Dec. date 14.11.16 - TC 1642381 | 50 |
| 8428.39.00 GRAIN CONVEYORS, TROUGH CHAIN, having ALL of the following: (a) one-way direction conveying troughs with return rolls AND inspection window; (b) throughput capacity NOT exceeding 100 t/h; (c) conveyor velocity NOT greater than 0.65 m/s; (d) angle inclination NOT greater than 15 degrees Op. 22.08.16 Dec. date 14.11.16 - TC 1644446 | 50 |
| 8436.29.00 POULTRY LAYING AND REARING CAGE SYSTEM, with OR without tiltable platforms, including BOTH of the following: (a) multiple tiered perches; (b) winch powered feeding AND drinking vessel connectors Op. 24.08.16 Dec. date 14.11.16 - TC 1645344 | 50 |

Description of Goods including the
Customs Tariff Classification

Schedule 4 Item Number

| 8438.90.10 | PARTS, PLANETARY MIXER, being ANY of the following: | 50 | |
|------------|---|--------------------|--------------|
| | <ul style="list-style-type: none"> (a) whips OR whisks; (b) beaters OR beater paddles; (c) spiral hooks; (d) bowls; (e) control knobs OR buttons; (f) covers; (g) mounting plates; (h) upper AND/OR middle AND/OR lower machine bodies; (i) plugs; (j) bases; (k) boxes; (l) bowl lift shafts OR rods; (m) bushes; (n) bowl cradles; (o) bowl lift arms; (p) bowl lift rods; (q) handles; (r) strain reliefs OR relievers; (s) bowl latches OR clamps; (t) hubs; (u) cover plates; (v) planetary holders; (w) plates; (x) safety guards; (y) splash guards OR spill guards; (z) weld clips; (aa) ball sockets; (ab) selector arms; (ac) bowl lift connections; (ad) upright columns; (ae) clips; (af) shifter yokes; (ag) shifter yoke plungers; (ah) shifter guide rods; (ai) escort planks; (aj) net OR mesh grids; (ak) pillars; (al) selector arms; (am) retainers without bearings; (an) caps; (ao) sleeves; (ap) bowl lift eccentrics; (aq) spacers; (ar) hub attachments; (as) ventilation plates; (at) jackets; (au) slide sheaths; (av) support pieces OR tubes; (aw) hand wheels with OR without handles; (ax) fixed seats; (ay) view windows; (az) housing AND tube assemblies; (ba) outlet pipes; (bb) tubes; (bc) hand wheel handles; (bd) hub selector arms; (be) hub AND cam assemblies; (bf) cam assemblies; (bg) yokes; (bh) knobs | | |
| | Op. 16.08.16 | Dec. date 14.11.16 | - TC 1642383 |
| 8465.92.00 | PLASTIC PRESCRIPTION LENS CUTTING, EDGING AND DRILLING MACHINES | 50 | |
| | Op. 25.08.16 | Dec. date 14.11.16 | - TC 1645796 |
| 8479.89.90 | INSTALLATION AND REMOVAL PLATFORMS, CONTAINER TWISTLOCK, stand-alone OR crane mountable, programmable logic controlled | 50 | |
| | Op. 16.08.16 | Dec. date 14.11.16 | - TC 1642611 |

NOTIFICATION OF AN AUSTRALIAN INDUSTRY REVOCATION REQUEST - SECTION 269SC(1A) CUSTOMS ACT

Applications have been lodged for revocation of the Tariff Concession Orders set out in the following TABLE.

The Lodgement Request Date shown in the table below is the intended revocation date for the Tariff Concession Order which will take effect should the application for revocation be successful.

Importations not covered by in-transit provisions may be subject to post action as any decision to revoke an order is backdated to the date of request for revocation.

THE TABLE

| Description of Goods including the Customs Tariff Classification | Schedule 4 Item Number Lodgement Request Date |
|--|--|
|--|--|

| | | |
|------------|--|----------------|
| 7209.17.00 | STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not coated, in coils, having ALL of the following; (a) yield strength NOT greater than 210 MPa; (b) tensile strength NOT less than 250 MPa; (c) total elongation NOT less than 40%; (d) in ANY of the following sizes: (i) thickness 0.75 mm and width 1 150 mm; (ii) thickness 0.75 mm and width 1 435 mm; (iii) thickness 0.75 mm and width 1 565 mm; (iv) thickness 0.75 mm and width 1 640 mm; (v) thickness 0.75 mm and width 1 700 mm; (vi) thickness 0.80 mm and width 1 220 mm; (vii) thickness 0.80 mm and width 1 565 mm; (viii) thickness 0.80 mm and width 1 580 mm; (ix) thickness 0.80 mm and width 1 584 mm; (x) thickness 0.80 mm and width 1 585 mm; (xi) thickness 0.80 mm and width 1 590 mm; (xii) thickness 0.80 mm and width 1 625 mm; (xiii) thickness 0.85 mm and width 1 730 mm; | 50 07.11.16 |
|------------|--|----------------|

For the purposes of this Order, tolerances allowable for specification (d) are:

(a) thickness +/- 10%

(b) width +/- 1%

Op. 24.12.12

Dec. date 18.03.13

- TC 1248927

| | | |
|------------|--|----------------|
| 7209.17.00 | STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not coated, in coils, having ALL of the following: (a) yield strength NOT less than 185 MPa; (b) tensile strength NOT less than 340 MPa; (c) total elongation NOT less than 32%; (d) in ANY of the following sizes: (i) thickness 0.70 mm and width 1 235 mm; (ii) thickness 0.70 mm and width 1 350 mm; (iii) thickness 0.70 mm and width 1 425 mm; (iv) thickness 0.70 mm and width 1 450 mm; (v) thickness 0.70 mm and width 1 453 mm; (vi) thickness 0.70 mm and width 1 470 mm; (vii) thickness 0.70 mm and width 1 485 mm; (viii) thickness 0.70 mm and width 1 510 mm; (ix) thickness 0.70 mm and width 1 520 mm; (x) thickness 0.70 mm and width 1 530 mm; (xi) thickness 0.75 mm and width 1 390 mm; (xii) thickness 0.75 mm and width 1 525 mm; (xiii) thickness 0.75 mm and width 1 555 mm; (xiv) thickness 0.75 mm and width 1 710 mm; (xv) thickness 0.75 mm and width 1 740 mm; (xvi) thickness 0.75 mm and width 1 800 mm; (xvii) thickness 0.80 mm and width 1 435 mm; (xviii) thickness 0.80 mm and width 1 585 mm; | 50 07.11.16 |
|------------|--|----------------|

For the purposes of this Order, tolerances allowable for specification (d) are:

(Continued on next page)

Description of Goods including the
Customs Tariff ClassificationSchedule 4 Item Number
Lodgement Request Date

(Continued from previous page)

- (a) thickness +/- 10%
-
- (b) width +/- 1%

Op. 24.12.12

Dec. date 18.03.13

- TC 1248928

7209.17.00 STEEL, flat rolled, non-alloy, cold rolled, not
coated, in coils, having ALL of the following:50
07.11.16

- (a) yield strength NOT greater than 250 MPa;
-
- (b) tensile strength NOT less than 270 MPa;
-
- (c) elongation NOT less than 35%;
-
- (d) in ANY of the following sizes:
-
- (i) thickness 0.60 mm and width 1 700 mm;
-
- (ii) thickness 0.60 mm and width 1 710 mm;
-
- (iii) thickness 0.60 mm and width 1 780 mm;
-
- (iv) thickness 0.65 mm and width 1 560 mm;
-
- (v) thickness 0.70 mm and width 1 600 mm;
-
- (vi) thickness 0.80 mm and width 1 730 mm;
-
- (vii) thickness 0.80 mm and width 1 775 mm;
-
- (viii) thickness 1.00 mm and width 1 588 mm

For the purposes of this Order, tolerances allowable for
specification (d) are:

- (a) thickness +/- 10%
-
- (b) width +/- 1%

Op. 27.03.13

Dec. date 17.06.13

- TC 1310743

7209.17.00 STEEL, flat rolled, non-alloy, cold rolled, not coated,
in coils, having ALL of the following:50
07.11.16

- (a) yield strength NOT greater than 250 MPa;
-
- (b) tensile strength NOT less than 250 MPa;
-
- (c) elongation NOT less than 35%;
-
- (d) in ANY of the following sizes:
-
- (i) thickness 0.67 mm and width 1 050 mm;
-
- (ii) thickness 0.67 mm and width 1 065 mm;
-
- (iii) thickness 0.67 mm and width 1 080 mm;
-
- (iv) thickness 0.70 mm and width 915 mm;
-
- (v) thickness 0.70 mm and width 1 020 mm;
-
- (vi) thickness 0.70 mm and width 1 050 mm;
-
- (vii) thickness 0.70 mm and width 1 230 mm;
-
- (viii) thickness 0.70 mm and width 1 275 mm;
-
- (ix) thickness 0.70 mm and width 1 285 mm;
-
- (x) thickness 0.70 mm and width 1 400 mm;
-
- (xi) thickness 0.72 mm and width 840 mm;
-
- (xii) thickness 0.72 mm and width 1 030 mm;
-
- (xiii) thickness 0.72 mm and width 1 500 mm;
-
- (xiv) thickness 0.75 mm and width 1 150 mm;
-
- (xv) thickness 0.75 mm and width 1 220 mm;
-
- (xvi) thickness 0.75 mm and width 1 370 mm;
-
- (xvii) thickness 0.75 mm and width 1 410 mm;
-
- (xviii) thickness 0.75 mm and width 1 420 mm;
-
- (xix) thickness 0.75 mm and width 1 425 mm;
-
- (xx) thickness 0.75 mm and width 1 435 mm;
-
- (xxi) thickness 0.75 mm and width 1 450 mm;
-
- (xxii) thickness 0.75 mm and width 1 455 mm;
-
- (xxiii) thickness 0.75 mm and width 1 490 mm;
-
- (xxiv) thickness 0.76 mm and width 660 mm;
-
- (xxv) thickness 0.76 mm and width 675 mm;
-
- (xxvi) thickness 0.76 mm and width 1 080 mm;
-
- (xxvii) thickness 0.76 mm and width 1 120 mm;
-
- (xxviii) thickness 0.76 mm and width 1 420 mm;
-
- (xxix) thickness 0.80 mm and width 600 mm;
-
- (xxx) thickness 0.80 mm and width 620 mm;
-
- (xxxii) thickness 0.80 mm and width 660 mm;
-
- (xxxiii) thickness 0.80 mm and width 785 mm;
-
- (xxxiv) thickness 0.80 mm and width 850 mm;
-
- (xxxv) thickness 0.80 mm and width 900 mm;

(Continued on next page)

Description of Goods including the
Customs Tariff ClassificationSchedule 4 Item Number
Lodgement Request Date

(Continued from previous page)

- (xxxv) thickness 0.80 mm and width 1 010 mm;
- (xxxvi) thickness 0.80 mm and width 1 140 mm;
- (xxxvii) thickness 0.80 mm and width 1 220 mm;
- (xxxviii) thickness 0.80 mm and width 1 270 mm;
- (xxxix) thickness 0.80 mm and width 1 570 mm;
- (xl) thickness 0.80 mm and width 1 584 mm;
- (xli) thickness 0.85 mm and width 995 mm;
- (xlii) thickness 0.85 mm and width 1 140 mm;
- (xliii) thickness 0.85 mm and width 1 300 mm;
- (xliv) thickness 0.85 mm and width 1 484 mm;
- (xlv) thickness 0.90 mm and width 1 060 mm;
- (xlvi) thickness 0.95 mm and width 820 mm;
- (xlvii) thickness 0.95 mm and width 930 mm;
- (xlviii) thickness 0.95 mm and width 990 mm;
- (xlix) thickness 0.95 mm and width 1 100 mm;
- (l) thickness 0.95 mm and width 1 105 mm;
- (li) thickness 0.95 mm and width 1 130 mm;
- (lii) thickness 0.95 mm and width 1 170 mm;
- (liii) thickness 0.95 mm and width 1 290 mm;
- (liv) thickness 0.95 mm and width 1 302 mm;
- (lv) thickness 0.95 mm and width 1 770 mm;
- (lvi) thickness 1.00 mm and width 765 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

Op. 09.04.13

Dec. date 24.06.13

- TC 1312159

7210.49.00

STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:

50
07.11.16

- (a) yield strength NOT greater than 210 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 40%;
- (d) total coating mass NOT less than 30 g/m² and NOT greater than 70 g/m² on each side;
- (e) in ANY of the following sizes:
 - (i) thickness 0.75 mm and width 1 390 mm;
 - (ii) thickness 0.75 mm and width 1 450 mm;
 - (iii) thickness 0.75 mm and width 1 475 mm;
 - (iv) thickness 0.75 mm and width 1 530 mm;
 - (v) thickness 0.75 mm and width 1 565 mm;
 - (vi) thickness 0.75 mm and width 1 640 mm;
 - (vii) thickness 0.76 mm and width 1 220 mm;
 - (viii) thickness 0.80 mm and width 1 350 mm;
 - (ix) thickness 0.95 mm and width 820 mm;
 - (x) thickness 1.00 mm and width 624 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

Op. 24.12.12

Dec. date 18.03.13

- TC 1248929

7210.49.00

STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:

50
07.11.16

- (a) yield strength NOT less than 190 MPa;
- (b) tensile strength NOT less than 340 MPa;
- (c) total elongation NOT less than 32%;
- (d) total coating mass NOT less than 30 g/m² and NOT greater than 70 g/m² on each side;
- (e) in ANY of the following sizes:
 - (i) thickness 0.70 mm and width 865 mm;
 - (ii) thickness 0.70 mm and width 980 mm;
 - (iii) thickness 0.70 mm and width 1 225 mm;
 - (iv) thickness 0.70 mm and width 1 244 mm;

(Continued on next page)

Description of Goods including the
Customs Tariff ClassificationSchedule 4 Item Number
Lodgement Request Date

(Continued from previous page)

- (v) thickness 0.70 mm and width 1 300 mm;
- (vi) thickness 0.70 mm and width 1 350 mm;
- (vii) thickness 0.70 mm and width 1 370 mm;
- (viii) thickness 0.70 mm and width 1 400 mm;
- (ix) thickness 0.70 mm and width 1 410 mm;
- (x) thickness 0.70 mm and width 1 455 mm;
- (xi) thickness 0.70 mm and width 1 500 mm;
- (xii) thickness 0.70 mm and width 1 585 mm;
- (xiii) thickness 0.70 mm and width 1 710 mm;
- (xiv) thickness 0.70 mm and width 1 720 mm;
- (xv) thickness 0.65 mm and width 865 mm;
- (xvi) thickness 0.65 mm and width 1 800 mm;
- (xvii) thickness 1.00 mm and width 1 160 mm

For the purposes of this Order, tolerances allowable for
specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

Op. 24.12.12

Dec. date 18.03.13

- TC 1248930

- 7210.49.00 STEEL, flat rolled, non-alloy, hot dipped galvanized zinc coated, in coils, having ALL of the following:
- (a) yield strength NOT less than 190 MPa;
 - (b) tensile strength NOT less than 340 MPa;
 - (c) elongation NOT less than 32%;
 - (d) coating mass NOT less than 30 g/m² and NOT greater than 70 g/m² on each side;
 - (e) in EITHER of the following sizes:
 - (i) thickness 0.70 mm and width 1 740 mm;
 - (ii) thickness 1.00 mm and width 1 225 mm

50
07.11.16For the purposes of this Order, tolerances allowable for
specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

Op. 04.03.13

Dec. date 13.05.13

- TC 1307948

- 8309.90.00 CLOSURES, COMPOSITE CAN END, hermetically sealable, having a diameter NOT less than 80mm

Op. 14.04.15

Dec. date 25.05.15

- TC 1519042

50
07.11.16

- 8309.90.00 CLOSURES, COMPOSITE CAN END, comprising ALL of the following:

- (a) outer ring;
- (b) aluminium foil membrane;
- (c) plug;
- (d) diameter NOT less than 80mm

Op. 14.04.15

Dec. date 25.05.15

- TC 1519043

50
07.11.16